

PROFESSIONAL FM TRANSCEIVER

**T520** 



## Hi-Capacity Li-ion Battery

LONG TIME STANDBY

# High Power Dutput

FREQUENCY RANGE 400~480MHz

## **FEATURES**

**Built-in CTCSS & DCS** Software Encryption Function Chinese/English Voice Prompt







### **MAIN FEATURES**

- VOX Transmmit Function
- High-Capacity Li-ion Battery pack
- Programmable by PC
- High Frequency Stability
- Power Saving Function

- 16 Programmable Channels
- Built-in CTCSS/DCS
- Wide/Narrow Band Selectable
- Time out Timer
- Chinese/English Voice Prompt

#### **SPECIFICATION**

GENERAL	
Frequency Range	UHF: 400~480MHz
Operating Temperature	-20°C~+60°C
Frequency Combination	Phase lock frequency synthesize
Frequency Stability	±2.5ppm
Memory Channel	16 Channels
Working voltage	DC 7.4V
Antenna Impedance	50Ω
Operating Mode	Simplex of co-frequency or alien frequency
Dimension	100×50×28mm (without antenna)
Weight	210g (Include Battery Pack)

Notice: Saving your presence, no additional notice will be sent if specification
changes because of technology-improving.

TRANSMIT PART	
RF Power	≤5W
Modulate Mode (W/N)	16КФF3E,11КФF3E
Max. Freq. Deviation (W/N)	<5K / <2.5KHz
Remain Wave Radiation	<-60dB
Transmitting Current	≤1300mA

RECEIVE PART	
Sensitivity	<0.20µV(12dB SINAD)
Squelch Sensitivity	<0.16µV
Intermodulation Antijamming	50dB
Audio Power output	500mW
Receiving Current	≤100mA
Squelch Standby	20mA

QUANZHOU TIANNENG ELECTRONICS CO., LTD. **TEAMUP (HK) ELECTRONIC LIMITED** 

